



Primary and Second Driveways

The following chart illustrates the requirements for Primary and Secondary Driveways. For a comprehensive list of development standards for Primary and Secondary Driveways, please refer to the indicated sections of the West Covina Municipal Code.

Requirements	Primary Driveway (Sec. 26-402.5 WCMC)	Secondary Driveway (Sec. 26-402.5 WCMC)	Circular Driveway
Purpose	Direct access from the street to a garage or carport as defined in Sec. 26-402.5	Providing access to the rear or side yard for the parking or storage of recreational vehicles, recreational equipment and trailers, and/or trailers in the side or rear yards.	
Length Restrictions	22 feet minimum	None	None
Width of Driveway	Minimum= Garage width + 6 feet (Width of primary driveway should have pavement of 6 feet on either or both sides of the garage or carport driveway) OR Maximum= Garage width + 12 feet (an additional 12 feet on one side of the driveway)	10 feet minimum 12 feet maximum	10 feet minimum 12 feet maximum
Standard Driveway Approach	12 feet minimum 24 feet maximum	12 feet minimum and maximum	12 feet minimum and maximum
Driveway Materials	Portland cement concrete Asphalt concrete	Grass-crete Turf-block Ribbon	Portland cement concrete Asphalt concrete
Restriction(s)	None	No vehicles may be parked or stored on the secondary driveway in the front yard. Must be fully screened.	22 feet minimum between approaches
Review Process	None	Administrative Use Permit	Staff Review